







40/41



inductive

IP69K

		PFM	PFK	PFM-26	PFK-26
					
dimensions		M12	M18	M12	M18
standard shielded		2 mm	5 mm	2 mm	5 mm
standard unshielded		4 mm	8 mm	4 mm	8 mm
long distance shielded		4 mm	8 mm	—	—
long distance unshielded		8 mm	12 mm	—	—
standard housing		●	●	●	●
short housing		—	—	—	—
miniaturized housing		—	—	—	—
power supply	Vdc	●	●	●	●
	Vac	—	—	—	—
output type	NPN - NO	●	●	—	—
	NPN - NC	—	—	—	—
	PNP - NO	●	●	—	—
	PNP - NC	—	—	—	—
	PNP - NO + NC	●	●	●	●
	NPN - NO + NC	●	●	●	●
	DECOUT®	—	—	—	—
	SCR	—	—	—	—
	0...10 V	—	—	—	—
	4...20 mA	—	—	—	—
temperature range		-40°C...+80°C	-40°C...+80°C	-25°C...+110°C	-25°C...+110°C
protection degree		IP68/IP69K	IP68/IP69K	IP68/IP69K	IP68/IP69K
housing material		stainless steel AISI316L	stainless steel AISI316L	stainless steel AISI316L	stainless steel AISI316L
active head material		PPS	PPS	PPS	PPS
output	cable	—	—	—	—
	M8 plug	—	—	—	—
	M12 plug	●	●	●	●
ATEX		II3GD	II3GD	—	—
other certifications		